

TAKE-A-NUMBER REFLECTIVE INDICATOR



SPECIFICATIONS

MODELS

From one to five rows with two or three digits for the number and one or two for the service point.

Digits:

100 mm high, 60 mm width, 7 segments magnetic biestables high visibility reflective surface.

2 or 3 digits for the numbers
1, 1.5(*) or 2 dígitos for the service points

Digit colors: yellow and white.

Service points: up to 16.

Visibility: 50 m.

Power supply: 220 Vac, -15/+10%.

Dimensions in cm:

Rows	Width	Height	Depth
1	39	22	7.5
2	68	48	11
3	68	63	11
4	68	78	11
5	68	93	11

Enclosure:

Steel textured powder coating finished.

Maximum distance between push button cables and board: 50 m.

Communications

RS232 or Ethernet network

(*) Up to 19 service points could be represented.

The customers avoid to stand in a line.

Eliminates multiple queues allowing a more uniform attention.

Maintains the customers away from the stations.

Specially designed for customized attention.

FUNCTION

Calling the customers that previously took consecutive numbers from a ticket dispenser.

APPLICATIONS

Banks, tax collectors, paperwork attention, governmental institutions.

FEATURES

High visibility, low consumption, maintenance free, long lasting, maintenance free.

OPERATION

The customers take consecutive numbers from a ticket dispenser. Then are called by arrival order.

When a service point is available, the employee press the increment push button and the number and service point are displayed in the first row of the board, accompanying with a tone.

Using a different push button the employee could repeat the calling.

The previous numbers go down losing the last one.

Options: data reception by serial line, 15 cm digits, enclosure color.

